

**NOIV7.E53505****Auxiliary Devices for Use in Hazardous Locations Certified for Canada**[Page Bottom](#)**Auxiliary Devices for Use in Hazardous Locations Certified for Canada**[See General Information for Auxiliary Devices for Use in Hazardous Locations Certified for Canada](#)

ADALET/SCOTT FETZER CO
 4801 W 150TH ST
 CLEVELAND, OH 44135-3301 USA

E53505

Pilot lights: Open type.

Class I, Groups B, C and D; Class II, Groups E, F and G.

Cat. Nos. XL or XLS, followed by A, B, C, G, R or W, followed by (Blank), A, B, C, G or R, followed by (Blank), S or L, may be followed by (Blank), followed by T, followed by -G, followed by H, followed by 5, 6, 12, 24, 30, 36, 45, 60, 75, 120 or 135, followed by suffix N4.

Cat. No. XLX followed by S or blank, followed by R, A, G, B or W, followed by 5 through 120 or 240 followed by blank, C or G.

Illuminated Pilot Lights, Cat. No. XLP, followed by S or blank, followed by A, R, G or W, followed by X, followed by 12, 24 or 120.

Class I, Groups B, C and D; Class II, Groups E, F and G.

Cat. No. XHK followed by 82 through 105, followed by C, followed by ZZ, followed by C, L or R, followed by Z, may be followed by N4.

Cat. No. XHKS followed by 82 through 105, followed by C, followed by ZZ, followed by C, L or R, followed by Z, may be followed by N4.

Cat. No. XHK followed by 223 through 282, followed by C, followed by ZZ, followed by C, L or R, followed by Z, may be followed by N4.

Cat. No. XHKS followed by 223 through 282, followed by C, followed by ZZ, followed by C, L or R, followed by Z, may be followed by N4.

Cat. No. XHS followed by 6 through 29, followed by C, followed by B, BL, C, G, GD or R, followed by B, G or R, followed by ZZ, may be followed by N4.

Cat. No. XHSS followed by 6 through 29, followed by C, followed by B, BL, C, G, GD or R, followed by B, G or R, followed by ZZ, may be followed by N4.

Cat. No. XHS followed by 111 through 182, followed by C, followed by B, BL, C, G, GD or R, followed by B, G or R, followed by ZZ, may be followed by N4.

Cat. No. XHSS followed by 111 through 182, followed by C, followed by B, BL, C, G, GD or R, followed by B, G or R, followed by ZZ, may be followed by N4.

Cat. No. XHS followed by 283 through 306, followed by CZZZZ, may be followed by N4.

Cat. No. XHSS followed by 283 through 306, followed by CZZZZ, may be followed by N4.

Class I, Groups B, C and D; Class II, Groups E, F and G.

Cat. No. XHD followed by 72 through 81, followed by CB, followed by BB, GB, GG, RB, RG or RR, followed by ZZ, may be followed by N4.

Cat. No. XHDS followed by 72 through 81, followed by CB, followed by BB, GB, GG, RB, RG or RR, followed by ZZ, may be followed by N4.

Cat. No. XHD followed by 322 through 331, followed by CB, followed by BB, GB, GG, RB, RG or RR, followed by ZZ, may be followed by N4.

Cat. No. XHDS followed by 322 through 331, followed by CB, followed by BB, GB, GG, RB, RG or RR, followed by ZZ, may be followed by N4.

Selector switches: Open Type

Class I, Groups B, C and D; Class II, Groups E, F and G.

Cat. No. XHD followed by 332 through 336, followed by D, followed by BB, GB, GG, RB, RG or RR, followed by BB, GB, GG, RB, RG or RR, followed by ZZ, may be followed by N4.

Cat. No. XHDS followed by 332 through 336, followed by D, followed by BB, GB, GG, RB, RG or RR, followed by BB, GB, GG, RB, RG or RR, followed by ZZ, may be followed by N4.

Cat. No. XHDM followed by 356 through 360, followed by D, followed by B or R, followed by B or R, followed by ZZ, may be followed by N4.

Cat. No. XHDM followed by 356 through 360, followed by D, followed by B or R, followed by B or R, followed by ZZ, may be followed by N4.

Cat. No. XHP followed by 1 through 5, followed by C or D, followed by B, BL, C, G, GD or R, followed by B, G or R, followed by ZZ, may be followed by N4.

Cat. No. XHPS followed by 1 through 5, followed by C or D, followed by B, BL, C, G, GD or R, followed by B, G or R, followed by ZZ, may be followed by N4.

Cat. No. XHM followed by 106 through 110, followed by C or D, followed by B or R, followed by B or R, followed by ZZ, may be followed by N4.

Cat. No. XHMS followed by 106 through 110, followed by C or D, followed by B or R, followed by B or R, followed by ZZ, may be followed by N4.

Cat. No. XHP followed by 307 through 311, followed by C or D, followed by ZZZZ, may be followed by N4.

Cat. No. XHPS followed by 307 through 331, followed by C or D, followed by ZZZZ, may be followed by N4.

Cat. No. XHM followed by 312 through 316, followed by C or D, followed by ZRZZ, may be followed by N4.

Cat. No. XHMS followed by 312 through 316, followed by C or D, followed by ZRZZ, may be followed by N4.

Cat. Nos. XHPPM followed by N4.

Cat. Nos. XHPPMS followed by N4.

Cat. Nos. XHPPM-TTR, may be followed by N4.

Cat. Nos. XHPPMS-TTR, may be followed by N4.

Dual push-buttons: Open Type

Class I, Groups C and D; Class II, Groups E, F and G.

Pilot light, push-button operator with guard, panel mounting, Series XLP-G, Cat. No. XLP, followed A, B, C, G, R, or W, may be followed by (Blank) or L, followed by (blank) or T, followed by -G, followed by 120, 60, 48, 28, 24, 12 or 6, may be followed by 30C, 31C, 32C, 33C or 34C, may be followed by N4.

Pilot light, push-button operator with guard, surface mounting, Series XLPS-G, Cat. Nos. XLPS followed by A, B, C, G, R, or W, followed by S, may be followed by (Blank) or L, may be followed by (Blank) or T, followed by -G, followed by 120, 60, 48, 28, 24, 12 or 6 may be followed by 30C, 31C, 32C, 33C or 34C, may be followed by N4.

Last Updated on 2015-08-19

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".