

Guarded LED Indicator Lights



XL_L-GH

FEATURES

- Suitable for long barrel and short barrel applications. All candelabra base LED lights can be relamped from the front by removal of the lens cap.
- Made with 3/4" NPSM threads.
- All LED indicator lights have 8" flexible leads, other lengths on special order, or screw terminal.
- Add suffix T to P/N for screw terminal.
- All lens caps are black anodized aluminum finish with colored glass lens.
- **Maximum installation thickness:** 1-11/16" on Long Barrel (Long Series), 5/8" on Short Barrel (Short Series).

LED Advantages:

- 10 Year/100,000 hour service life under normal ambient conditions.
- Up to 4x more energy efficient.
- Improved resistance to shock and vibration.
- LEDs operate significantly cooler than traditional lamps.
- Ultra bright cluster LED's.

STANDARD SERIES

Long Barrel Cat #	Short Barrel Cat #	Description	Weight (lbs.)
XLRL-GH	XLSRL-GH	Red	½
XLAL-GH	XLSAL-GH	Amber	½
XLGL-GH	XLSGL-GH	Green	½
XLWL-GH	XLSWL-GH	White	½
XLBL-GH	XLSBL-GH	Blue	½

*Add suffix T to P/N for screw terminal (Example: XLRLT-GH)

120V dual polarity supplied as standard.

12 or 24 volts optional, consult factory.

Certifications

Class I, Division 1, Groups B, C & D
 Class II, Groups E, F & G
 NEMA 3, 4, 7 & 9 / IP66

