



**XCE 0611 COVER**

- COVER OPENING TO BE MADE IN XCE ONLY.
- NOTES:
1. MINIMUM SPACING FROM CENTER OF OPERATOR TO NEAREST FLAT IS 1/4".
  2. MINIMUM SPACING BETWEEN 3-14 NPSM OPERATOR CENTERS IS 2/8 FOR THIS ENCLOSURE.
  3. MAXIMUM NUMBER OF OPERATORS IS 3.
  4. DIMENSION FROM CENTER LINE OF COVER FOR OPERATORS.
  5. DIMENSION FROM CENTER LINE AND BACK OF MFG. LUG FOR CONDUIT.
  6. FOR MFG. ENCLOSURE USE 5/8 BOLT.

		MODIFIED XCE/XAF 061105 ENCLOSURE FOR	
DATE: 4-20-01 BY: DDH CHECKED: 1-2 APPROVED: D TUMBAJAST XCE/XAF 061105	DATE: 4-20-01 BY: DDH CHECKED: 1-2 APPROVED: D TUMBAJAST XCE/XAF 061105	DATE: 4-20-01 BY: DDH CHECKED: 1-2 APPROVED: D TUMBAJAST XCE/XAF 061105	DATE: 4-20-01 BY: DDH CHECKED: 1-2 APPROVED: D TUMBAJAST XCE/XAF 061105