



OPTIONAL XHF-2 HINGES

OPTIONAL MTG. PAN

EXISTING GRD. SCREW

XCE 1824 COVER

- NOTES:
1. MINIMUM SPACING FROM CENTER OF OPERATOR TO NEAREST FLAT IS 1 1/8.
 2. MINIMUM SPACING BETWEEN 3/16 NPSM OPERATOR CENTERS IS 3/8 FOR THIS ENCLOSURE.
 3. MAXIMUM NUMBER OF OPERATORS IS 24.
 4. DIMENSION FROM CENTER LINES OF COVER FOR OPERATORS.
 5. DIMENSION FROM CENTER LINES OF BACK OF MFG. LOG FOR CONDUIT.
 6. FOR MFG. ENCLOSURE USE 1/2 BOLT.

		MODIFIED XCE/XHF 182406 ENCLOSURE FOR	
DATE: 11-16-01 BY: DDH CHECKED: 1-5 DESIGNED: D TUMBLAST XCE/XHF 182406	DATE: 11-16-01 BY: DDH CHECKED: 1-5 DESIGNED: D TUMBLAST XCE/XHF 182406	DATE: 11-16-01 BY: DDH CHECKED: 1-5 DESIGNED: D TUMBLAST XCE/XHF 182406	DATE: 11-16-01 BY: DDH CHECKED: 1-5 DESIGNED: D TUMBLAST XCE/XHF 182406