3-3/16" ID Enclosures

3-Lug Mounting

XIH housings are designed for small to medium size electronic assemblies. The 3-3/16" ID provides ample clearance to accommodate a wide variety of measurement and control devices. Precision machined from sand-cast copper-free aluminum.


STANDARD FEATURES


- · 3 factory drilled mounting lugs
- Four interior mounting bosses at 45° orientation accommodate blind tapped holes on a 2-1/2" bolt circle. Consult factory for other mounting options.
- 1/2" conduit feed-through hubs, offset for maximum clearance and capacity
- Internal and external ground screws and tamper resistant cover set screw for extra safety
- Glass cover models have a 2-5/8" diameter, tempered glass window for local read out
- Buna-Nitrile rubber gasket for NEMA Type 4X watertight applications
- Corrosion resistant, "safety blue" polyester powder coating (other colors available)
- · Stainless steel hardware


DESIGN OPTIONS

- 1/4-20 UNC holes in front boss for bracket mounting. Consult factory for other sizes.
- Front Boss Modifications: 1/2" or 3/4" NPT entry for sensor, probe or conduit entry.
 NPSM & metric entries also available, consult factory.
- Other interior mounting bosses available please consult factory
- High ambient silicone gasket (+70°C)











Solid Cover Arrangements




SOLID COVER	
Catalog Number	Description
XIHFCX 2L-3 Lug	Flat Cover, 1/2" NPT Hubs




SOLID COVER		
Catalog Number	Description	
XIHDCX 2L-3 Lug	Dome Cover,- 1/2" NPT Hubs	

Glass Cover Arrangements



GLASS COVER	
Catalog Number	Description
XIHFGCX 2L-3 Lug	Flat Glass Cover, 1/2" NPT Hubs



GLASS COVER	
Catalog Number	Description
XIHDGCX 2L-3 Lug	Dome Glass Cover, 1/2" NPT Hubs